

PATENT

x No. 24180-667000

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

enske et al. U.S. Patent Application) 169/470,386 Filed: December 22, 1999 mail, addressed to:

Multilayer Film Structures Having Improved Seal and Tear Properties

Examiner: M. Jackson Group Art Unit: 1773

Certificate of Mailing

I hereby certify that on March 26, 2001, this correspondence was deposited with the United States Postal Service, first class

Assistant Commissioner for Patents Washington, DC 20231.

Scherrer, Registration No. 45,080

AMENDMENT

Assistant Commissioner for Patents Washington, DC 20231

Dear Sir:

ir:

This amendment is submitted in response to the Office Action dated October 25, Please amend the above-identified application as follows:

In the Specification:

Please replace the paragraph beginning at page 5, line 25, with the following rewritten paragraph:

4-First layer (1) comprises poly(ethylene) or blended poly(ethylene) wherein the poly(ethylene) has a density range from about 0.93 g/cc to about 0.97 g/cc. Poly(ethylenes) having this density range are exemplified by medium density poly(ethylene) (MDPE) and highdensity poly(ethylene) (HDPE). A preferred density range for the poly(ethylene) of said layer is from about 0.94 g/cc to about 0.965 g/cc. Poly(ethylenes) having this density range are exemplified by HDPE. A particularly preferred poly(ethylene) for said first layer is high density poly(ethylene) (HDPE) having a density of about 0.96 g/cc. HDPE can further be exemplified by Equistar-Alathon® M-6060 HDPE.

Please replace the paragraph beginning at page 6, line 4, with the following rewritten 03/30/2001 YPOLITE1 00000081 130206 09470386 paragraph:

83 EC: 183

160.00 CH